



SpeedMixer™

German Engineering
by Hauschild



DAC 600 FVZ / VAC-P / LR



Please scan
for more
information
about our
products.





SpeedMixer™

GermanEngineering
by Hauschild

Technical Data

	600.1 FVZ	600.2 VAC-P	600.1 FVZ LR	600.2 VAC-P LR
Mixing Capacity ¹ (g)	Up to 600	Up to 600	Up to 600	Up to 600
Speed (rpm)	800 – 2350	800 – 2350	800 – 2100	800 – 2100
Mixing time (s)	1 – 600	1 – 600	1 – 600	1 – 600
Voltage (V)/ Frequency (Hz)	230 / 50 – 60	230 / 50 – 60	230 / 50 – 60	230 / 50 – 60
Power consumption (kW)	1,2	1,2	1,2	1,2
Height – Lid open (mm)	960	1030	960	1030
Width (mm)	440	440	440	440
Depth (mm)	640	700	640	700
Weight (kg)	70	90	70	90
Vacuum option	no	yes	no	yes
LR Option – high performance	no	no	yes	yes
Additional features	Touch screen Vision panel Variable speed Selectable fixed speed 20 programme storage spaces Key lock (QS) Imbalance sensor RS-232 interface			

¹ incl. material, mixing cup, cup holder. These values are nominal and they might change depending on the physical characteristics of the material.

Subject to modifications – Last update 29/01/2020



Hauschild & Co. KG
 Waterkamp 1 · 59075 Hamm / Germany
 Phone +49 (0)2381 48205-0
 Telefax +49 (0)2381 48205-17
 E-Mail info@speedmixer.de
 www.speedmixer.de